

- ▶ **Newest DSP digital signal processing technology**
- ▶ **1/4 Sony CCD**
- ▶ **Mirror images function**
- ▶ **Case optional**

**CCTV SYSTEM**

www.svcard.com / www.securityhitech.com

Specification

Mode	TW-969
Pickup device:	1/4-inch Sony CCD
Number of pixels	PAL: 512 x 582 (V), NTSC: 512 (H) x 492 (V)
System of signal:	PAL/NTSC
Horizontal resolution:	420TV line
Minimum illumination:	0.03Lux/F1.2
Lens mount:	C/CS
Backlight compensation:	on/off (optional)
Electronic shutter:	1/50, 1/60 to 1/100,000 seconds
AGC:	on/off (optional)
White balance:	on/off (optional)
S/N ratio:	>48dB
Gamma correction:	>0.45
Operation temperature:	-20 to 50 degrees Celsius
Sync. system:	internal
Video output:	1.0V p-p /75 Ohms
Power consumption:	12V DC, <150mA 24V AC, <120mA 220V AC, <10mA
Dimensions (L x W x H):	119 x 59 x 54mm
Weight:	239g



S&V COMMUNICATION SERVICE NETWORK CO.,LTD.
 15/241-3 Sukhumvit 107 North Samrong
 Samutprakam,Thailand,10270
 Tel No. 02-759-2255 : Fax No.02-759-2980
www.svcard.com / www.securityhitech.com

■ Distributed By

