

# ACCESS CONTROL SYSTEM

Access Control Reader **TW-506**



ACCESS CONTROL



CARD &amp; KEY TAG



PASSWORD

[www.svcard.com](http://www.svcard.com) / [www.securityhitech.com](http://www.securityhitech.com)

## Specification

TW-506

- Input Voltage : 12 VDC (Linear Power Supply)
- Current Consumption : 80 – 130 mA
- Operation temperature : -5°C – 55°C
- Operation Humidity : 0 – 90 % Rh
- Case Material : ABS
- Proximity Card Type : EM Compatible
- RF Frequency : 125K Hz
- R/W Type : Read Only Type
- Reading Range : 10 – 20 cm
- Watch – Dog Self - reset
- 10.7(W) x 12.3(H) x 2.1(D) cm
- Weigh : 180 g
- Indoor Installation
- Signal Output : Wiegand 26 or 36 Bits
- ABA II
- RS - 485



S&V COMMUNICATION SERVICE NETWORK CO.,LTD.  
 15/241-3 Sukhumvit 107 North Samrong  
 Samutprakam,Thailand,10270  
 Tel No. 02-759-2255 : Fax No.02-759-2980  
[www.svcard.com](http://www.svcard.com) / [www.securityhitech.com](http://www.securityhitech.com)

■ Distributed By

