

Receipt Printer **SRP-370/372 THERMAL****Features****Additional Features**

- *Fast 200mm per Second Print Speed (One-Color Print)
- *Compatible with Competitor's Emulations Including Epson, Star, Citizen
- *Saves Installation Space (Compact Size, Wall Mount Option)
- *Paper-End Sensor / Near-End Sensor
- *Easy To Use Software Utilities : Virtual Memory Switch Manager, Non-Volatile Image Download, Firmware Download

**CARPARK SYSTEM**

www.svcard.com / www.securityhitech.com

Specification

SRP-370/372 THERMAL

Printer Speed-	
Mono :	200mm per Second / 61.7 Lines per Second
Bar Code :	100mm per Second / 30.9 Lines per Second
2-Color :	90mm per Second / 27.8 Lines per Second
Printing Method : Direct Thermal	
Resolution : SRP-370 =180 dpi / SRP-372 = 203 dpi	
Characters Per Line : Font A:42; Font B: 56	
Characters Per Line : Font A: 12x24; Font B: 9x17	
Paper Size : 57.5mm / 79.5mm / 82.5mm x 105mm Max. Diameter	
Paper Supply : Drop and Print	
Reliability (MCBF)-	
Printer :	70,000,000 Lines
Auto Cutter :	1,000,000 Cuts
TPH :	150 Km
Character Set : Alphanumeric: 95 International: 32	
Extended Graphic : 128 x 7 Page	
Barcode-	
1D:	EAN-13, EAN-8, CODE 39, Code 128, ITF, Codabar, UPC-A UPC-E
2D(Optional) :	PDF417, QR Code
Emulation : Epson , Citizen, Star	
Interface : Serial, Parallel, USB, Ethernet and Bluetooth	
Driver : WIN 95/98/ME/200/NT/XP/2003 Server/USB/OPOS	
Buzzer : Internal (Standard)	
Drawer Port : 1 Port (Maximum 2 Drawers)	
Data Buffer : 64 Kb	
Power Supply : AC 120~230 V 10% Adapter Included	
Power Consumption : Standby : 28.8W; Operating: 55.2W	
Operating Temperature : 32° ~ 112° F (0 ~ 45°C)	
Operating Humidity : 10% ~ 90% (Non-Condensing)	
Dimensions : 5-11/16" Wx7-9 / 16"Lx5-7/8" H	
Options : Splash Proof Cover	
	Wall Mount Bracket



S&V COMMUNICATION SERVICE NETWORK CO.,LTD.
 15/241-3 Sukhumvit 107 North Samrong
 Samutprakam,Thailand,10270
 Tel No. 02-759-2255 : Fax No.02-759-2980
www.svcard.com / www.securityhitech.com

■ Distributed By

