

ACCESS CONTROL SYSTEM

Proximity Reader TW-942



ACCESS CONTROL



CARD & KEY CARD



PASSWORD

www.svcard.com / www.securityhitech.com

Features

- Modern Designs With Non – Metal Shell
- Waterproof and Weather Resistant Functions
- Keystroke Backlight
- Reading Rang : up to 5-8 cm
- Card appliance : 125 kHz EM cards
- Chang Codes 1 Master, 1,000 users Proximity Card
- Door Open Detection
- Electric Lock, External push Switch
- Magnetic Contacts, Alarm
- Non-Volatile / EEprom Memory
- Option : Wiegand 26 bit Output
- Application Luxurious office Building, bank, Server Room, etc.

Specification

- | | |
|-------------------------|---|
| - DC Supply Voltage | Low Voltage input 12+10% VDC |
| - Current Consumption | 100 mA @ quiescent maximum |
| - Door Relay | 5 Amp 12 VDC |
| - Alarm Output Load | 150 mA Pull Current |
| - Tamper Protection | Negative Loop, normally closed |
| - Codes | 1 master, 1,000 cards and 1,000 codes |
| - Keypad | 12 keys, 3 LED Status Indicators |
| - Card Types | EM or EM Compatible |
| - Induction Distance | 5-8 cm |
| - Wiring Connections | Electric Lock, Remote Door Control, Door Open Detection, External Door Bell, External Alarm |
| - Memory | Non Volatile EEprom Memory |
| - Operating Temperature | 0C° to 60C° |
| - Keypad Housing | ABS High Impact Plastic |
| - Dimensions | 165 mm x 90 mm x 32 mm |
| - Weight | 250 g |



S&V COMMUNICATION SERVICE NETWORK CO.,LTD.
15/241-3 Sukhumvit 107 North Samrong
Samutprakam,Thailand,10270
Tel No. 02-759-2255 - Fax No.02-759-2980
www.svcard.com / www.securityhitech.com

■ Distributed By

